


Features

1. Monolithic inorganic material construction.
2. Closed magnetic circuit avoids crosstalk.
3. S.M.T. type.
4. Suitable for reflow soldering.
5. Shapes and dimensions follow E.I.A. spec.
6. Available in various sizes.
7. Excellent solderability and heat resistance.
8. High reliability. Reliability test meet AEC-Q200.
9. 100% Lead(Pb) & Halogen-Free and RoHS compliant.
10. Operating Temperature: -55~+150°C (Including self-temperature rise)



Certificate
of
Green Partner

Dimensions



Chip Size	
A	1.00±0.10
B	0.50±0.10
C	0.50±0.10
D	0.25±0.10

Units: mm

Part Numbering



A: Series
 B: Dimension L x W
 C: Material Lead Free Material
 D: Category Code V=Vehicle
 E: Impedance 121=120Ω
 F: Packaging T=Taping and Reel, B=Bulk(Bags)
 G: Rated Current 01=100mA

Specification

Tai-Tech Part Number	Impedance (Ω)	Test Frequency (MHz)	DC Resistance (Ω) max.	Rated Current (mA) max.
FCM1005KV-300T03	30±25%	100	0.20	300
FCM1005KV-600T03	60±25%	100	0.25	300
FCM1005KV-121T01	120±25%	100	0.30	100
FCM1005KV-151T01	150±25%	100	0.30	100
FCM1005KV-221T01	220±25%	100	0.40	100
FCM1005KV-301T01	300±25%	100	0.50	100
FCM1005KV-471T01	470±25%	100	0.65	100
FCM1005KV-601T00	600±25%	100	0.80	80
FCM1005KV-102T00	1000±25%	100	1.20	50
FCM1005MV-600T01	60±25%	100	0.30	100
FCM1005MV-121T00	120±25%	100	0.45	80
FCM1005MV-221T00	220±25%	100	0.60	50
FCM1005MV-301T00	300±25%	100	0.75	50

Impedance Frequency Characteristics(Typical)

