

SMD Power Inductor

TMPC1003HV-Series(G)-D

1. Features


1. Carbonyl Powder.
2. Compact design.
3. High current · low DCR · high efficiency.
4. Very low acoustic noise and very low leakage flux noise.
5. High reliability.
6. 100% Lead(Pb)-Free and RoHS compliant.
7. High reliability -Reliability test complied to AEC-Q200.
8. Operating temperature -55~+125℃(Including self - temperature rise)




2. Applications

Note PC power system · incl. IMVP-6
DC/DC converter .

3. Dimensions




leadframe



non-leadframe



Recommend PC Board Pattern




Series	A(mm)	B(mm)	C(mm)	D(mm)	E(mm)
TMPC1003HV	11.0±0.5	10.0±0.3	2.8±0.2	2.3±0.3	See Spec table

L(mm)	G(mm)	H(mm)
13.6	5.4	3.5

Note: 1. The above PCB layout reference only.
2. Recommend solder paste thickness at 0.15mm and above.

4. Part Numbering



A: Series
B: Dimension
C: Type
D: Inductance
E: Inductance Tolerance
F: Code

BxC
Magnetic metal powder
1R0=1.00uH
K=±10%, L=±15%, M=±20%, N=±25%, Y=±30%.
Marking: Black.1R0 and 2019(20 YY, 19 WW, follow production date).

5. Specification

Part Number	Inductance L0 (uH)±20%	I rms (A)	I sat (A)	DCR (mΩ) Typ. @25°C	DCR (mΩ) Max. @25°C	E(mm) ±0.3	Type
TMPC1003HV-R22MG-D	0.22	30	55	1.1	1.3	2.5	non-leadframe
TMPC1003HV-R33MG-D	0.33	25	47	1.2	1.5	2.5	non-leadframe
TMPC1003HV-R36MG-D	0.36	23	40	1.3	1.6	2.5	non-leadframe
TMPC1003HV-R47MG-D	0.47	20	33	2.1	2.5	2.5	non-leadframe
TMPC1003HV-R56MG-D	0.56	16	24	2.6	3.0	3.0	leadframe
TMPC1003HV-R82MG-D	0.82	15	22	3.9	4.5	3.0	leadframe
TMPC1003HV-1R0MG-D	1.00	15	20	4.6	6.0	3.0	leadframe
TMPC1003HV-1R5MG-D	1.50	13	20	6.5	7.5	3.0	leadframe
TMPC1003HV-2R2MG-D	2.20	12	16	8.0	9.0	3.0	leadframe
TMPC1003HV-3R3MG-D	3.30	9	14	14.5	16	3.0	leadframe
TMPC1003HV-4R7MG-D	4.70	7	13	20.5	22.5	3.0	leadframe
TMPC1003HV-5R6MG-D	5.60	7	12	28	32.5	3.0	leadframe
TMPC1003HV-6R8MG-D	6.80	6.5	9.5	30.2	35	3.0	leadframe
TMPC1003HV-8R2MG-D	8.20	6	8.5	42	48	3.0	leadframe
TMPC1003HV-100MG-D	10.0	5	8	50	55	3.0	leadframe

Note:

1. Test frequency : Ls : 100KHz /1.0V.
2. All test data referenced to 25°C ambient.
3. Testing Instrument(or equ) : L: HP4284A,CH11025,CH3302,CH1320,CH1320S LCR METER / Rdc:CH16502,Agilent33420A MICRO OHMMETER.
4. Heat Rated Current (I rms) will cause the coil temperature rise approximately ΔT of 40°C
5. Saturation Current (I sat) will cause L0 to drop approximately 30%.
6. The part temperature (ambient + temp rise) should not exceed 125°C under worst case operating conditions.Circuit design,component,PCB trace size and thickness,airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
7. Special inquiries besides the above common used types can be met on your requirement.

6. Typical Performance Curves

