

SMD Power Inductor TMPC0604HV-Series(G)-D

1. Features


1. Carbonyl Powder.
2. Compact design.
3. High current · low DCR · high efficiency.
4. Very low acoustic noise and very low leakage flux noise.
5. High reliability.
6. 100% Lead(Pb)-Free and RoHS compliant.
7. High reliability -Reliability test complied to AEC-Q200.
8. Operating temperature: -55~+125°C (Including self-temperature rise)



2. Applications


Note PC power system · incl. IMVP-6
DC/DC converter .

3. Dimensions



| Series | A(mm) | A'(mm) | B(mm) | C(mm) | D(mm) | E(mm) |
|------------|---------|---------|---------|---------|----------|---------|
| TMPC0604HV | 7.3±0.3 | 6.7±0.3 | 6.6±0.3 | 3.8±0.2 | 1.8±0.30 | 3.0±0.3 |


Recommend PC Board Pattern



| L(mm) | G(mm) | H(mm) |
|-------|-------|-------|
| 8.4 | 2.5 | 3.5 |

Note: 1. The above PCB layout reference only.
2. Recommend solder paste thickness at 0.15mm and above.

4. Part Numbering



A: Series
 B: Dimension
 C: Type Carbonyl Powder V:vehicle.
 D: Inductance 4R7=4.70uH
 E: Inductance Tolerance M=±20%,Y=±30%
 F: 印 D/C 印字:黑色,4R7 及 D/C 1840(18 年,40 週期)(依實際生產日期而定)

5. Specification

| Part Number | Inductance L0 (uH)±20% @ 0 A | I rms (A) Typ. | I sat (A) Typ. | DCR (mΩ) Typ. @25°C | DCR (mΩ) Max. @25°C |
|--------------------|---------------------------------|-------------------|-------------------|---------------------------|---------------------------|
| TMPC0604HV-R12YG-D | 0.12±30% | 32 | 64 | 0.7 | 1.0 |
| TMPC0604HV-R15YG-D | 0.15±30% | 30 | 55 | 0.9 | 1.2 |
| TMPC0604HV-R47MG-D | 0.47 | 23 | 28 | 3 | 3.4 |
| TMPC0604HV-R56MG-D | 0.56 | 20 | 26 | 3.8 | 4.3 |
| TMPC0604HV-R68MG-D | 0.68 | 16 | 24 | 4.1 | 4.5 |
| TMPC0604HV-1R0MG-D | 1.00 | 14 | 22 | 6.8 | 8.0 |
| TMPC0604HV-1R5MG-D | 1.50 | 12 | 20 | 10 | 12 |
| TMPC0604HV-2R2MG-D | 2.20 | 9 | 14 | 11.5 | 14 |
| TMPC0604HV-4R7MG-D | 4.70 | 6 | 11 | 28 | 32.5 |
| TMPC0604HV-6R8MG-D | 6.80 | 4.5 | 8.5 | 44 | 50 |
| TMPC0604HV-8R2MG-D | 8.20 | 4.5 | 8 | 55 | 64 |
| TMPC0604HV-100MG-D | 10.0 | 4 | 7 | 64 | 72 |
| TMPC0604HV-150MG-D | 15.0 | 3.0 | 3.5 | 80 | 90 |
| TMPC0604HV-220MG-D | 22.0 | 2.5 | 3.5 | 120 | 145 |
| TMPC0604HV-330MG-D | 33.0 | 1.8 | 3.2 | 180 | 210 |

Note:

1. Test frequency : L : 100KHz /1.0V
2. All test data referenced to 25°C ambient.
3. Testing Instrument : L/Q: HP4284A,CH11025,CH3302,CH1320 ,CH1320S LCR METER / Rdc:CH16502,Agilent33420A MICRO OHMMETER.
4. Heat Rated Current (I rms) will cause the coil temperature rise approximately $\Delta t_{40}^{\circ}\text{C}$
5. Saturation Current (I sat) will cause L0 to drop approximately 30%.
6. The part temperature (ambient + temp rise) should not exceed 125°C under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.
7. Special inquiries besides the above common used types can be met on your requirement.

6. Typical Performance Curves

